

2/pvts

DEVICE AND METHOD FOR CONTROLLING A MACHINE TOOL

The present invention is directed to a device, as well as to a method for controlling a machine tool.

To machine workpieces on a numerically controlled machine tool, supplementary data are sometimes needed, which are stored in tabular form in data files outside of the actual machining program, i.e., NC program. Such supplementary data can include, for example, geometrical tool data, or, however, of compensation values for the tool geometry obtained from a workpiece measurement. Typically, the type and structure or organization of such supplementary data in a data file are dependent upon the particular machining technology and sometimes even upon the particular machine tool type. Accordingly, there is a great variety in the types and structures of such supplementary data in the corresponding data files.

When a particular machining program is executed, the need can arise for a specific machining task to access the supplementary data from the machining program. For example, it can become necessary to input tool compensation data in order to properly correct the tool radius on the basis of the input data. This, in turn, requires that the structure of the extracted supplementary data, i.e., the specific organization of the database in question already be known at the time the control software is created, and not first at the time the machining program is created. This means that the control manufacturer must know and take into consideration the database structures in question already at the time the control software is created. Thus, for example, at this point in time, one must already know in which line and/or column, i.e., cell, of such a database, specific supplementary data

are to be found. Then, it is no longer possible, later on, to use a data file having a supplementary-data structure, i.e., supplementary-data organization that deviates from the originally considered structure. Accordingly, the control software created in this manner is not to be utilized independently of a specific machining technology or independently of a special machine tool type.

The object of the present invention is, therefore, to provide a device, as well as a method for controlling a machine tool, which will enable supplementary data, which are organized in any way at all, to be flexibly utilized from a machining program, without the specific organization or structure of the supplementary data already being known ahead of time, in particular already at the time the control software is created.

This objective is achieved by a device having the features set forth in Claim 1.

Advantageous specific embodiments of the device according to the present invention are derived from the measures indicated in the claims which are dependent upon Claim 1.

In addition, the above-specified objective is achieved by a method having the features set forth in Claim 10.

Advantageous specific embodiments of the method according to the present invention are derived from the measures indicated in the claims which are dependent upon Claim 10.

The measures according to the present invention ensure that, from a machining program, supplementary data may be extracted from a database, without the specific type and structure of the database and the supplementary data stored therein having to be known already at the time the control software is created. Knowledge of the database in question and of its

specific organization is not needed until the actual machining program is created at the particular machine. This ensures that the control software, which is created at one time, may be utilized for the most diversified machining technologies and/or the most diversified machine tool types, which work in conjunction with supplementary data organized in various ways.

In one especially advantageous specific embodiment of the present invention, in the particular machining program, to retrieve supplementary data from a database of this kind, database access commands are used which are based on the SQL database language or on another standardized database language.

With respect to the particular database in which the supplementary data are stored, very diverse specific embodiments exist. These may be stored, for instance, spatially separated from the particular machine or from the particular machining program; they may just as well be stored locally with the machining program, etc.

Further advantages of the present invention and details pertaining thereto are derived from the following description of the attached drawing, whose figures show:

Figure 1 a very schematized block diagram illustration of an exemplary embodiment of the device according to the present invention;

Figure 2 an extract from a machining program which includes commands for inputting supplementary data.

On the basis of the two Figures 1 and 2, the device of the present invention, as well as the method of the present invention are elucidated in the following. In a very schematized form, Figure 1 shows one possible specific

embodiment of the device according to the present invention which is suited for numerically controlling a machine tool. The device according to the present invention essentially includes a processing unit 20 having various functional units, as well as a database 40. The functions of the various components are explained in greater detail in the following description.

In the present example, database 40 is configured so as to be spatially separate from processing unit 20 and is linked to the same via a communications channel 60, via which data are exchanged between processing unit 20 and database 40. Communications channel 60 may be implemented in a variety of ways, for instance in the form of a network or bus connection, or also as an Internet connection, etc. Alternatively, database 40 may also be fundamentally located in the immediate vicinity of processing unit 20.

As explained at the outset, supplementary data required for workpiece processing are stored in database 40. These may be very diversified types of supplementary data, such as the already mentioned tool compensation data, other supplementary data pertaining to tool geometry, and/or supplementary data pertaining to a specific machine tool type.

What is important, at this point, for the present invention is that the supplementary data, i.e., database 40, are able to be organized in any manner at all, i.e., particularly when creating the control software, the knowledge of the specific line-by-line or tabular organization of database 40 is not necessary. At this point in time, it is merely necessary then to know the logical structure of database 40 in question, i.e., which type of data are to be ultimately extracted from the database. Accordingly, the database in question may be configured both as a database that is organized in tabular form, as well as a commercially available database system. It is possible at this point, for instance, to use database 40 of

5

10

15

25

30

To ensure access to the supplementary data of arbitrarily organized database 40, specific measures in accordance with the present invention are needed on the part of processing unit 20, as explained in the following. To access

5 supplementary data from machining program 10, at this point, in conjunction with the database access commands, explicit knowledge of the specific database organization is no longer needed. It is, rather, commands from a standardized database language, such as SQL, which are used as database access
10 commands in machining program 10. They make it possible to read out data from a database without having to know the specific structure of the table.

For processing of machining program 10, processing unit 20 has
15 an input interface 21 for machining program 10. Configured downstream from input interface 21 is an interpreter unit 22, on the side of the processing unit. Besides executing the usual NC records in machining program 10, interpreter unit 22 also undertakes the correct processing of the database access
20 commands, which are likewise contained in machining program 10. Thus, the database access commands are identified as such by interpreter unit 22, and, for example, the retrieval of supplementary data from database 40 via a database interface 23 in processing unit 20 is organized by interpreter unit 22.
25 Supplementary data retrieved in this manner are subsequently fed to a conversion unit 24, which uses the supplementary data in the further course of the machining to execute machining program 10.

30 The above-explained functional units of processing unit 20, such as the various interfaces 21, 23, as well as interpreter unit 22, and conversion unit 24, are usually designed as software.

35 Illustrated downstream from processing unit 20 is merely block 50, which is intended to represent the machine tool that is controlled by the unit.

5
10

15

20

20

25

30

35

Via the following program line N130, values for length and

radius of tool type no. 2 are read out of database TOOL.

Finally, via program line N140, the exchange of tool no. 2 is initiated, and the allowances Q1 for the radius and Q2 for the
5 length read out of the database TOOL are considered.

Machining program 10 is selected in the usual manner via subsequent program lines N150.

10 Analogously to this example, data from databases organized in any way whatsoever are accessed in the manner of the present invention.